

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Original) A system providing network topology and bandwidth management comprising:
  - a connection module, said connection module capable of accepting inputs and providing outputs to various types of voice and non-voice data networks; and
  - a management module, said management module cooperating with the connection module to accept data from said voice and non-voice data networks for routing, wherein said routing comprises any of frequency shifting the data and/or time shifting the data such that the data may be communicated across the voice and non-voice networks, the management module performing at least one multiplexing operation to route multi-frequency signals to appropriate termination points cooperating with the management module which are selected based on the frequency of at least one component signal of the multi-frequency signals.
2. (Currently Amended) The system as recited in claim ~~2~~ 1, wherein the management module comprises a plurality of network adapters for use to connect to various voice and non-voice data networks.
3. (Currently Amended) The system as recited in claim ~~2~~ 1, further comprising a control circuit, the control circuit executing one or more instructions for use to determine ~~the~~ an origination of the data and ~~the~~ a destination of the data.
4. (Original) The system as recited in claim 3, wherein the control circuit selects an appropriate network adapter based on the origination and destination of the data.
5. (Original) The system as recited in claim 2, wherein the network adapters comprise any of: HPNA adapter, coaxial network adapter, Ethernet network adapter, wireless network adapter, POTS adapters, and power line network adapters.

6. (Currently Amended) The system as recited in claim 5, wherein the data is processed according to ~~the~~ a type of adapter.

7. (Currently Amended) The system as recited in claim 1, further comprising a computing application, the computing application having a user interface for use in configuring the ~~communication~~ connection and management modules.

8. (Original) The system as recited in claim 1, wherein the voice data networks comprise the public switched telephone network.

9. (Original) The system as recited in claim 1, wherein the non-voice data networks comprise any of the Internet, a LAN, a WAN, and a peer-to-peer network.

10. (Original) The system as recited in claim 1, wherein the management module is capable of processing various data communication protocols comprising any of IP, Ethernet and ATM.

11. (Original) A method for the management of network topology and bandwidth comprising the steps of:

determining the source of data for communication to a termination point, the termination point having a predetermined operational signal frequency;

based on the termination of data and the predetermined operational signal frequency, selecting the appropriate network topology adapter, wherein the network topology adapter comprises any of HPNA adapter, coaxial network adapter, Ethernet network adapter, wireless network adapter, POTS adapters, and power line network adapters; and

communicating the data to the termination point.

12. (Original) The method as recited in claim 11, further comprising routing the data using addressing information.

13. (Original) The method as recited in claim 12, further comprising configuring the adapters, wherein a computing application capable of configuring the adapters is used.

14. (Original) The method as recited in claim 11, further comprising executing at least one instruction set for use in selecting the appropriate adapter, the instruction set being executed by a control logic circuit.

15. (Original) The method as recited in claim 11, further comprising frequency and/or time shifting the data before communication to the termination point.

16. (Currently Amended) An apparatus for the management of network topology and bandwidth comprising:

an input module, the input module having ports to receive various network couplers from various voice and non-voice data networks;

a control module, the control module having at least one instruction set for execution to determine the source and destination points of data which is communicated across the apparatus to and from the various voice and non-voice data networks, the determination of source and destination points being performed based on the operational frequency ranges of the source and/or destination points; and

an output module, the output module cooperating with the control module to select an appropriate network adapter for use to communicate data to the destination point, ~~wherein the adapters comprise any of HPNA adapter, coaxial network adapter, Ethernet network adapter, wireless network adapter, POTS adapters, and power line network adapters, the network adapters being selected based on the operational frequency of the source and destination points.~~

17. (Original) The apparatus as recited in claim 16, further comprising:

a computing application interface, the computing application interface for use to communicate with at least one computing application for use in configuring the apparatus.

18. (Currently Amended) The apparatus as recited in claim 17 ~~further comprising~~, wherein the computing application comprises a Web browser interface.

19. (Original) The apparatus as recited in claim 16, wherein the output module comprises a plurality of output ports for use when routing data.

20. (Original) The apparatus as recited in claim 19, wherein the output ports comprise RJ-11 type ports.

21. (New) The apparatus as recited in claim 16, wherein the adapters comprise any of an HPNA adapter, coaxial network adapter, Ethernet network adapter, wireless network adapter, POTS adapters and a power line network adapter, the appropriate network adapter being selected based on the operational frequency of the source and destination points.

22. (New) A method for managing a network control device, the method comprising:  
accessing a graphical user interface having a topology management control  
and an application services gateway control;

activating the topology management control to execute one or more  
instructions to configure a network management device;  
activating the application services gateway control to execute one or more  
instructions to configure the network management device to operate with services provided  
by a telephone services provider; and

routing one or more of voice information and non-voice information through  
the configured network management device to network adapters, wherein the routing is  
performed based on at least one frequency component of one or more voice information and  
non-voice information networks.

23. (New) The method of claim 22, wherein activating the topology management control  
to execute one or more instructions to configure a network management device comprises  
selecting configuration information including one or more of network addressing  
information, encryption information and network/bandwidth topology information.

24 (New) The method of claim 22, wherein activating the application services gateway control to execute one or more instructions to configure the network management device comprises selecting services comprising one or more of video on demand, music on demand, remote security applications and video conferencing.

25.(New) The method of claim 22, wherein accessing a graphical user interface comprises navigating controls of the network management device using a computer browser application.

26. (New) The method of claim 22, wherein activating the topology management control further comprises manipulating controls for configuring one of a home network and a small office network.

27. (New) The method of claim 22, wherein routing one or more of voice information and non-voice information through the configured network management device to network adapters comprises routing network data packets to one or more of an HPNA adapter, a coaxial network adapter, an Ethernet network adapter, a wireless network adapter, a POTS adapter, and a power line network adapter.

28. (New) A computer-readable medium having computer-executable instructions for performing a method for managing a network control device, the method comprising:  
accessing a graphical user interface having a topology management control and an application services gateway control;  
activating the topology management control to execute one or more instructions to configure a network management device;  
activating the application services gateway control to execute one or more instructions to configure the network management device to operate with services provided by a telephone services provider; and  
routing one or more of voice information and non-voice information through the configured network management device to network adapters, wherein the routing is

performed based on at least one frequency component of one or more voice information and non-voice information networks.

29. (New) The computer-readable medium of claim 28, wherein the step of activating the topology management control to execute one or more instructions to configure a network management device comprises selecting configuration information including one or more of network addressing information, encryption information and network/bandwidth topology information.

30. (New) The computer-readable medium of claim 28, wherein the step of activating the application services gateway control to execute one or more instructions to configure the network management device comprises selecting services comprising one or more of video on demand, music on demand, remote security applications and video conferencing.

31.(New) The computer-readable medium of claim 28, wherein the step of accessing a graphical user interface comprises navigating controls of the network management device using a computer browser application.

32. (New) The computer-readable medium of claim 28, wherein the step of activating the topology management control further comprises manipulating controls for configuring one of a home network and a small office network.

33. (New) The computer-readable medium of claim 28, wherein the step of routing one or more of voice information and non-voice information through the configured network management device to network adapters comprises routing network data packets to one or more of an HPNA adapter, a coaxial network adapter, an Ethernet network adapter, a wireless network adapter, a POTS adapter, and a power line network adapter.

**DOCKET NO.:** BELL-0257/02382

**PATENT**

**Application No.:** 10/699,294

**Preliminary Amendment - First Action Not Yet Received**

**Amendments to the Drawings**

The attached sheet(s) of drawings includes changes to Fig(s) 2, 3, 5 and 7. The sheet(s), which includes Fig(s) 2, 3, 5 and 7 replaces the original sheet(s) including Fig(s) 2, 3, 5 and 7.

Attachment: Replacement Sheet(s)